

SCHWEIZER AIRCRAFT CORP.

Supplement to the FAA Approved  
Rotorcraft Flight Manual

For

300C Model 269C Helicopters

See Page 2 for Effectivity

**ROTORCRAFT AMPHIBIOUS FLOAT LANDING GEAR**

Part No. 269A4300-15

Date of Original Approval: 22 Mar 1972

Date of Reissue #1 Approval: 21 Sep 1988

Date of Revision #1 Approval: 04 Oct 1996

Date of Reissue #2 Approval: MAY 27 1998

Approved By: Michelle J. Maurer

Michele J. Maurer  
Manager, Systems and Flight Test  
Branch, NYACO, ANE-172

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

FAA APPROVED  
ROTORCRAFT FLIGHT MANUAL SUPPLEMENT  
ROTORCRAFT AMPHIBIOUS FLOAT LANDING GEAR  
PART NO. 269A4300-15  
FOR  
300C MODEL 269C HELICOPTERS

HELICOPTER SERIAL NO. EFFECTIVITY  
269C Serial No. 0140 and subsequent  
or Serial No. 0004 through 0139 having Schweizer Kit Part  
No. M10059-5 installed

**LOG OF PAGES**

PAGE	DATE	PAGE	DATE
1	27 May 1998	8	27 May 1998
2	27 May 1998	9	27 May 1998
3	27 May 1998	10	27 May 1998
4	27 May 1998	11	27 May 1998
5	27 May 1998	12	27 May 1998
6	27 May 1998	13	27 May 1998
7	27 May 1998	14	27 May 1998

**NOTE**

The change bar ( █ ) defines the latest FAA Approved changes.

### REVISION TABLE

Revision Number	Date	Description
Revision #1	Issued 22 Mar 1972	Per Drawing No. 269A4300-15
	Reissued 21 Sep 1988	Updated to reformat
	04 Oct 1996	Revised to correct typographical errors and other miscellaneous changes.
	Reissued 27 May 1998	Add limitation data for aircraft with three-piece chin skin, and miscellaneous format changes

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

This page intentionally left blank.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

Table of Contents

Section No.	Title	Page No.
Section I	Introduction and General	7
Section II	Limitations	8
Section III	Emergency and Malfunction Procedures	11
Section IV	Normal Procedures	12
Section V	Performance Data	13
Section VI	Weight & Balance	14
Section VII	Aircraft Handling, Service, and Maintenance	14
Section VIII	Additional Operations and Performance Data	14

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

This page is intentionally left blank.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

**Section I**  
Introduction and General

The 269A4300-15 Amphibious Float Landing Gear Kit consists of two multiple cell type inflatable floats, landing gear skid extensions and attachment fittings.

Except as modified by this Rotorcraft Flight Manual Supplement, operation in compliance with Section II of the basic FAA Approved Rotorcraft flight Manual is mandatory. Other sections of the RFM or Supplement are recommended procedures.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

**Section II**  
Limitations

2-1. CGLimits

<u>Longitudinal</u>	<u>Lateral</u>
95.0	+2.25, -1.0
99.5	+4.0, -1.75
101.0	+1.5, -2.0

**NOTE:** Lateral "+" is right of centerline, lateral "-" is left of centerline when looking forward.

- 2-2 The cylinder head temperature probe must be moved to cylinder number three for proper indication when floats are installed. The cylinder head temperature probe must be relocated to cylinder number two for the nonfloat configuration.
- 2-3. Aircraft S/N's 0004 through 0139 must be modified in accordance with Schweizer Kit P/N M10059-5 incorporating a tailboom mounted static source with 269A8310 and 269A8309-11 restrictor fittings.
- 2-4. Night flight with floats permitted if the following equipment is installed; landing, navigation (including 2 extra side position lights), anticollision lights and instrument lights.
- 2-5. Night operation, to and from water, limited to aircraft equipped with dual 450-watt (GE 4580, 28-volt) landing lights.



SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

- 2-6. Minimum float inflation pressure 1.5 psig; maximum float inflation pressure is 6 psig. To maintain these limits, changes in operating altitude should be considered as follows:

If the Initial Altitude Float Pressure is; (psig)	Allowable Altitude Increase is; (feet)	Allowable Altitude Decrease is; (feet)
1.5	9800	0
2	8800	1000
3	6600	3000
4	4400	5400
5	2200	7600
6	0	9800

**NOTE:** This will include the normal variation in ambient temperature associated with changes in altitude.

To account for variations in ambient temperature or water temperature at a given base of operations, the following criteria should be used to maintain the minimum 1.5 psig inflation pressure:

When an ambient (air) temperature or water temperature colder than the temperature at initial inflation is anticipated, float inflation pressure should be increased 0.5 psig (above the minimum 1.5 psig) for each 15 degrees decrease in temperature anticipated.

Example: Floats inflated to 1.5 psig

70°F Ambient temperature at time of inflation

45°F Anticipated water temperature at scheduled landing or parking site

25°F Temperature decrease

Pressure change to account for:

$$(25^{\circ} \div 15^{\circ}) \times 0.5 \text{ psig} = 0.8 \text{ psig}$$

Minimum float inflation pressure for this operation would be:

$$1.5 \text{ psig} + 0.8 \text{ psig} = 2.3 \text{ psig}$$

**NOTE:** Temperature increases will increase float inflation pressure, and need not be considered. However, 6 psig must not be exceeded.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

- 2-7. When a Muffler Kit (269A8801, 269A8801-3, or 269A8801-5) is installed with the Float Kit, the cooling air deflectors (269A8520, included in the 269A8801-3 or 269A8801-5 Muffler Kit) and the cooling baffle (269A5563, included in the Float Kit) must be installed and both side fairings (269A2303-3 and-4) removed.
- 2-8. Doors off operation permitted.
- If passenger seats are not occupied the center seat back must be fastened and right seat cushion removed (or lashed in place).
- 2-9. Takeoff and landing to and from water not permitted above 1900 pounds gross weight or if 269A4335 Quad Searchlight is installed.
- 2-10.  $V_{NE}$  above 1900 pounds gross weight is 101 mph IAS at sea level. Above sea level, reduce  $V_{NE}$  7 mph per 1000 feet of altitude.
- 2-11. On aircraft configured with the three-piece chin skin P/N 269A2329-7, the 269A2355-1 air scoop installation is required when the float kit is installed.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

**Section III**  
Emergency and Malfunction Procedures

3-1. Water Landing

- a. Engine Failure - Altitude Above 400 Feet
  - (1) Enter normal autorotation.
  - (2) Establish a steady glide of 60 mph IAS.
  - (3) At about 80 to 100 feet altitude apply back cyclic stick until aircraft is slightly nose high, decreasing forward speed and rate of decent.
  - (4) At about 2 to 10 feet altitude, increase collective to reduce sink rate. Make water contact slightly nose high.
  - (5) Avoid rapid lowering of collective after landing.
- b. Engine failure - altitude above 7 feet and below 400 feet. Use procedure outlined in basic flight manual except make water contact slightly nose high. (If altitude and airspeed permit, the procedure outlined in 3-1a. above should be followed.)
- c. Engine failure - altitude below 7 feet. Follow procedure outlined in basic flight manual.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

**Section IV**  
Normal Procedures

- 4-1. Pilot's Preflight Inspection - On helicopters equipped with 269A2355-1 Air Scoop Installation, inspect intake scoop for foreign objects and debris.
- 4-2. Rotor Engagement on Water - Determine that sufficient clearance exists between aircraft and any obstacle during rotor engagement. Tail swing before directional control is obtained will be approximately 200 degrees.
- 4-3. Water touchdown speed should be less than 30 mph. Reduce speed if water is rough.
- 4-4. On water landing the collective should not be fully lowered until forward speed is 5 mph or less.
- 4-5. Water taxi speed should be less than 10 mph. A slight application of collective pitch may be used to increase speed, but speed should be kept down so the bows of the floats do not submerge.

For cross-wind taxiing, apply a slight amount of cyclic in order to maintain correct control of the helicopter.

- 4-6. Hover for approximately 10 seconds to allow water to drain from pitot tube following operations involving moderately high bow waves.
- 4-7. Night Operations - Water

**NOTE:** Use both landing lights for all water landings.

a. Normal Night Water Landings

- (1) Slow airspeed to approximately 55 mph for normal approach and reduce collective for desired rate of descent  
Maintain 3200 rpm.
- (2) At about 80 to 100 feet altitude raise the nose of the aircraft slightly, reducing airspeed and rate of descent.
- (3) Make water contact slightly nose high.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

- (4) Avoid rapid lowering of collective after landing.
- b. During night takeoff from water, switch to aft landing light to reduce glare.
- 4-8. Ballast may be required when in solo flight and can be added by the use of the 269A4314-17 weight kit. Ballast consists of a 2.5-pound bag, 45-pound weight, and 20-pound weight. Maximum ballast is 65 pounds.
- 4-9. When ballast is air transported in or on the helicopter it should be stowed and secured.

**NOTE:** No storage between seats with center collective installed.

**Section V**  
Performance Data

- 5-1. On aircraft S/N's 0059 and subsequent and on earlier aircraft modified in accordance with SAC Kit P/N M10059-5 with the 269A4600-9 or -13 airspeed indicator, relocating the static source to the tailboom, the performance data in the basic Approved Rotorcraft Flight Manual " b" or " c" configurations is applicable.

SCHWEIZER MODEL 269 SERIES HELICOPTER  
CSP-C-1B

**Section VI**  
Weight and Balance

6-1. Float installation center of gravity limits are shown under Limitations, Section II. Weight and balance calculation should use the following information to ensure these center of gravity limitations are not exceeded:

Part No.	ITEM Description	Weight (lbs)	Arm (inches)
269A4300-15	Float Installation	58.2	118.6
269A4314-9	Ballast Bag	2.5	52.5
269A4314-7	Weight		
	In Ballast Bag	45.0	52.5
	In Seat	45.0	79.0
269A4314-9	Weight		
	In Ballast Bag	20.0	52.5
	In Seat	20.0	79.0
269A2355-1	Air Scoop Installation	1.50	46.0

**Section VII**  
Aircraft Handling, Service, and Maintenance  
Not Affected

**Section VIII**  
Additional Operations and Performance Data  
Not Affected